

RC-V8TR-HD Series

8-CHANNEL DIGITALLY ENCODED
HD-CVI/TVI/AHD VIDEO TRANSCIVER




OVERVIEW

RC-V8T/R-HD Series video transmitter and receiver transmit eight channels of 10-bit digitally encoded HD-CVI, AHD or HD-TVI video transmission over one core single mode or multimode fiber. Optimized optical modules which are compatible with 25/30/50/60F@720P and 25/30F@1080P ensure the highest performance for most demanding CCTV applications. The hot-pluggable and adjustment-free design ensures the convenience of the installation and operation. The modules are available in either standalone or rack mount versions.

APPLICATIONS

- Analog HD CCTV(Fixed Video)
- Intelligent transportation systems (ITS)
- Security and surveillance
- Access Control

SYSTEM DESIGN



FEATURES

- 10-Bit Digitally Encoded Uncompressed Transmission
- Compatible with NTSC, PAL or SECAM Video Standards
- High Performance Laser-based Optics
- Plug-and-play Design with No Adjustment Required
- Local LED Indicators to Monitor System Status
- Wide Optical Dynamic Range
- No EMI, RFI, Cross Talk and Video Distortion
- Support up to 30KM
- No Video Degradation and Optical Attenuation
- Multimode or Singlemode Fiber
- Standalone or Rack Mount Options

RC-V8TR-HD Series

8-Channel Digital Encoded HD-CVI/TVI/AHD Video Transceiver

SPECIFICATIONS

Video

Video Input	1 volt pk-pk (75 ohms)
Video Voltage Range	0.6~2.0Vp-p
Video Input/Output Channels	8
Bandwidth	60 MHz
Bit Resolution	10-bit
Differential Gain	1%
Differential Phase	<1°
Tilt	< 1%
Up/down time	<0.8ns
Max. Shake	<0.2 UI
Reflection Loss	>15dB
S/N Ratio	> 60dB (Weighted)

Optical

Wavelength	1310nm, Multimode 1310nm, Singlemode
Optical Emitter	Laser Diode
Number of Fibers	1

Indicating LEDs

Power Present
Video Present

Connectors

Optical	ST or SC
Video	BNC

General

Power Supply	AC100-240V
Size	485x 220x 45mm
Construction:	Aluminum
Finish:	Paint
MTBF:	> 100,000 hours
Operating Temp	-35° C to + 65°C
Storage Temp	-40° C to +85°C



ORDERING INFORMATION

Part Number	Description	Fiber	Optical PWR Budget	Max Distance
RC-V8TS-HD	8-Channel HD-CVI/TVI/AHD Video TX	Singlemode	20dB	30KM
RC-V8RS-HD	8-Channel HD-CVI/TVI/AHD Video RX	Singlemode	20dB	30KM
RC-V8TM-HD	8-Channel HD-CVI/TVI/AHD Video TX	Multimode	14dB	500M
RC-V8RM-HD	8-Channel HD-CVI/TVI/AHD Video RX	Multimode	14dB	500M

*Optical transmission distance is limited to optical loss of the fiber and any additional loss introduced by connectors, splices and patch panels.